



TECHNICAL DATA REPORT



FROM THE RESEARCH & DEVELOPMENT LABORATORIES OF MOMAR, INC.

ODOUR CAP

Correspondence address:
P O Box 2257
CLAREINCH
7740

Benefits:

- * Floats on water.
- * Non-toxic, safe to use.
- * Improves lift station efficiency.
- * Puts a "cap" on objectionable odors instantly.
- * Will not rust parts, components, and any other metal surfaces.
- * Dissolves grease and slime in lift stations, cesspools, and grease traps.



Application:

For Lift Stations: Pour directly into manhole or lift station pit. For Best results, use sufficient quantities to assure a **2 to 10 cm** cap on the surface. (Example: To create a **2 cm** cap in a **1.8 m** diameter lift station pit, add **50 litres**)

For Septic Tanks and Cesspools: Add **1 litre** per **20000 litre** capacity for initial treatment. Use **30 to 60 ml** per week for each **2000 litre** capacity as preventative maintenance treatment.

For Grease Traps: Pour one-half cup (**125 ml**) of concentrate into drains. Allow to remain overnight. Treat repeatedly as needed.

Specifications:

| | |
|--|-------------------------------|
| pH @ 25°C (ASTM-E-70) | N/A |
| Density @ 25°C (ASTM-D-287) | 0.83 gm per ml |
| Color (visual) | None |
| Appearance @ 25°C (visual) | Clear |
| Foam Height | None |
| Odor | Citrus |
| Health / Flammability / Reactivity | 1 / 2 / 0 |
| Personal Protection | B - Safety glasses and gloves |

MOMAR

8 Induland Crescent, Lansdowne, Cape Town
Tel: 021-6921295 Fax: 021-6913898 Toll Free: 0800 012053
Email: orders@momar.co.za